

C-10 / C-12 UPRATE - ABILITY & COMPARISION CHART



INDEX	
C-10 / C-12 UPRATE - ABILITY AND COMPARISION CHART	
PAGE 1	C-12 2KS72000 & UP (JULY 2001 TO PRESENT)
PAGE 2	C-12 2KS40000 - 71999 (JANUARY 2000 TO JULY 2001)
PAGE 3	C-12 2KS1 - 39999 (NOVEMBER 1998 TO JANUARY 2000)
PAGE 4	C-12 9NS (SEPTEMBER 1997 TO NOVEMBER 1998)
PAGE 5	C-12 1YN (MARCH 1995 TO SEPTEMBER 1997)
PAGE 6	C-10 3CS 23000 & UP (JULY 2001 TO PRESENT)
PAGE 7	C-10 3CS 12000 - 22999 (JANUARY 2000 TO JULY 2001)
PAGE 8	C-10 3CS1 - 11999 (NOVEMBER 1998 TO JANUARY 2000)
PAGE 9	C-10 8YS (SEPTEMBER 1997 TO NOVEMBER 1998)
PAGE 10	C-10 2PN (MARCH 1995 TO SEPTEMBER 1997)
PAGE 11&12	FLASH FILE PART NUMBER PROGRESSION
PAGE 13	C-10 TURBO CHART
PAGE 14	C-12 TURBO CHART

C-12 2KS72000 & UP UPRATE - ABILITY AND COMPARISION CHART

2KS72000 - UP	335 / 1550 2100	355 / 1350 1800	355 / 1350 2100	380 / 1450 1800	380 / 1450 2100	395 / 1450 1800	395 / 1450 2100	410 / 1550 1800	410 / 1450 2100	410 / 1550 2100	410 / 1450 1800	430 / 1650 2100	430 / 1650 1800
CORE ARR.G.	165-0608	165-0609	165-0609	136-4310	136-4310	165-0612	165-0612	136-4311	136-4311	136-4311	136-4311	132-3198	132-3198
MAX H.P.	420	370	370	395	395	410	410	425	425	425	415	445	445
TORQ. RISE	85%	30%	52%	30%	52%	25%	46%	29%	41%	51%	21%	53%	31%
FLASH FILE	215-7360	215-7361	215-7361	215-7362	215-7362	215-7363	215-7363	215-7366	215-7366	215-7366	215-7366	215-7369	215-7369
INTER-LOCK	50	51	51	52	52	53	53	56	56	56	56	59	59
PERFORMANCE	0K3839	0K3857	0K3840	0K3858	0K3841	0K3859	0K3842	0K3861	0K3843	0K3844	0K3860	0K3851	0K3862
PERF DATA	DM7138	DM7166	DM7139	DM7170	DM7142	DM7169	DM7145	DM7162	DM7146	DM7149	DM7159	DM7152	DM7157

MULTI-TORQUE

2KS72000 - UP	355/410 MT	355/410 MT	355/410 MT	380/410 MT	380/430 MT
MULTI-TORQUE	1350/1550 1800	1350/1450 1800	1350/1450 2100	1450/1550 1800	1450/1650 1800

CORE ARR.G.	165-0614	165-0614	165-0614	165-0616	165-0620
MAX H.P.	370/425	370/415	370/425	395/425	395/445
TORQ. RISE	30/30 %	30/21 %	52/41 %	31/30 %	31/32 %
FLASH FILE	215-7364	215-7364	215-7364	215-7365	215-7368
INTER-LOCK	54	54	54	55	58
PERFORMANCE	0K3866	0K3864	0K3846	0K3868	0K3870
	0K3865	0K3863	0K3845	0K3867	0K3869
PERF DATA	DM7163	DM7160	DM7147	DM7164	DM7144
	DM7168	DM7167	DM7140	DM7171	DM7172

EMERGENCY / RV / BUS

425 / 1450 2100	425 / 1550 2100	455 / 1550 2100
--------------------	--------------------	--------------------

132-3198	165-0615	165-0621
425	425	455
41%	51%	44%
215-7367	215-7367	215-7370
57	57	60
0K3847	0K3848	0K3852
DM7154	DM7155	DM7156

ALL ARRANGEMENTS ABOVE HAVE COMMON IRON

SPECIAL RATINGS

AIR INLET SHUTOFF

2KS72000 - UP	430 / 1650 1800	430 / 1650 2100	REQUIRES IRON CHANGE
AIR SHUTOFF			
CORE ARR.G.	155-7979	155-7979	SHUTOFF GP. 163-2586
MAX H.P.	445	445	WIRING HARNESS 189-9151
TORQ. RISE	31%	53%	
FLASH FILE	215-7372	215-7372	
INTER-LOCK	62	62	
PERFORMANCE	0K2789	0K2788	
PERF DATA	DM6007	DM6006	

EMERGENCY / RV / BUS

505 / 1550 2100	REQUIRES IRON CHANGE
195-6605	TOP RING 195-6599
505	BOTTOM RING 195-6601
31%	PISTON COOLING JET 195-6606
215-7373	
61	
0K3856	
DM7143	

C-12 2KS40000 - 71999 UPRATE - ABILITY AND COMPARISION CHART

2KS40000 - UP	335 / 1550 2100	355 / 1350 1800	355 / 1350 2100	380 / 1450 1800	380 / 1450 2100	395 / 1450 1800	395 / 1450 2100	410 / 1550 1800	410 / 1450 2100	410 / 1550 2100	410 / 1450 1800	430 / 1650 2100	430 / 1650 1800
CORE ARR.	165-608	165-0609	165-0609	136-4310	136-4310	165-0612	165-0612	136-4311	136-4311	136-4311	136-4311	132-3198	132-3198
MAX H.P.	420	370	370	395	395	410	410	425	425	425	415	445	445
TORQ. RISE	85%	30%	52%	30%	52%	25%	46%	29%	41%	51%	21%	53%	31%
FLASH FILE	220-6623	220-6624	220-6624	220-6625	220-6625	220-6627	220-6627	220-6631	220-6631	220-6631	220-6631	220-6634	220-6634
INTER-LOCK	20	21	21	22	22	23	23	26	26	26	26	29	29
PERFORMANCE	0K1961	0K1962	0K1963	0K1964	0K1965	0K1966	0K1967	0K1976	0K1979	0K1978	0K1977	0K1984	0K1985
PERF DATA	DM4846	DM4847	DM4848	DM4849	DM4850	DM6000	DM6001	DM6002	DM6005	DM6004	DM6003	DM6006	DM6007

MULTI-TORQUE

2KS40000 - UP	355/410 MT	355/410 MT	355/410 MT	380/410 MT	380/430 MT
MULTI-TORQUE	1350/1550 1800	1350/1450 1800	1350/1450 2100	1450/1550 1800	1450/1650 1800

CORE ARR.	165-0614	165-0614	165-0614	165-0616	165-0620
MAX H.P.	370/425	370/415	370/425	395/425	395/445
TORQ. RISE	30/30 %	30/21 %	52/41 %	31/30 %	31/32 %
FLASH FILE	220-6629	220-6629	220-6629	220-6630	220-6633
INTER-LOCK	24	24	24	25	28
PERFORMANCE	0K1969	0K1971	0K1973	0K1975	0K1983
	0K1968	0K1970	0K1972	0K1974	0K1982
PERF DATA	DM6009	DM6011	DM6013	DM6015	DM6017
	DM6008	DM6010	DM6012	DM6014	DM6016

EMERGENCY / RV / BUS

425 / 1450 2100	425 / 1550 2100	455 / 1550 2100
--------------------	--------------------	--------------------

132-3198	165-0615	165-0621
425	425	455
41%	51%	44%
220-6632	220-6632	220-6635
27	27	30
0K1980	0K1981	0K1986
DM6018	DM6019	DM6020

ALL ARRANGEMENTS ABOVE HAVE COMMON IRON

SPECIAL RATINGS

AIR INLET SHUTOFF

2KS40000 - UP	430 / 1650 1800	430 / 1650 2100	REQUIRES IRON CHANGE
AIR SHUTOFF			
CORE ARR.	155-7979	155-7979	SHUTOFF GP. 163-2586
MAX H.P.	445	445	WIRING HARNESS 189-9151
TORQ. RISE	31%	53%	
FLASH FILE	220-6638	220-6638	
INTER-LOCK	34	34	
PERFORMANCE	0K2789	0K2788	
PERF DATA	DM6007	DM6006	

EMERGENCY / RV / BUS

505 / 1550 2100	REQUIRES IRON CHANGE
195-6605	TOP RING 195-6599
505	BOTTOM RING 195-6601
31%	PISTON COOLING JET 195-6606
220-6636	
31	
0K2835	
DM6254	

C-12 2KS1 - 39999 UPRATE - ABILITY AND COMPARISION CHART

2KS1-39999	335 / 1550 2100	355 / 1350 1800	355 / 1350 2100	380 / 1450 1800	380 / 1450 2100	395 / 1450 1800	395 / 1450 2100	410 / 1550 1800	410 / 1450 1800	410 / 1550 2100	410 / 1450 1800	430 / 1650 2100	430 / 1650 1800
CORE ARR.	165-608	165-0609	165-0609	136-4310	136-4310	165-0612	165-0612	136-4311	136-4311	136-4311	136-4311	132-3198	132-3198
MAX H.P.	420	370	370	395	395	410	410	415	425	425	425	445	445
TORQ. RISE	85%	30%	52%	30%	52%	25%	25%	21%	29%	51%	41%	53%	31%
FLASH FILE	215-7811	215-7812	215-7812	215-7813	215-7813	215-7815	215-7815	215-7816	215-7816	215-7816	215-7816	215-7822	215-7822
INTER-LOCK	11	12	12	4	4	6	6	7	7	7	7	8	8
PERFORMANCE	0K1342	0K2298	0K6138	0K2272	0K2273	0K2274	0K2274	0K2277	0K2276	0K2278	0K2279	0K2280	0K2281
PERF DATA	DM4820	DM6137	DM6138	DM6139	DM6140	DM6141	DM6141	DM6144	DM6143	DM6145	DM6146	DM6147	DM6149

MULTI-TORQUE

2KS1-39999	355/410 MT	355/410 MT	355/410 MT	380/410 MT	380/430MT4	380/430MT2
MULTI-TORQUE	1350/1550	1350/1450	1350/1450	1450/1550	1450/1650	1450/1650
	1800	1800	2100	1800	1800	1800
CORE ARR.	165-0614	165-0614	165-0614	165-0616	165-0620	165-0613
MAX H.P.	370/425	370/415	370/425	395/425	395/445	395/445
TORQ. RISE	30/29%	30/21 %	52/41 %	30/29%	30/31%	30/31%
FLASH FILE	215-7817	215-7817	215-7817	215-7818	215-7820	215-7819
INTER-LOCK	3	3	3	9	10	14
PERFORMANCE	0K2283	0K2285	0K2287	0K2289	0K2291	0K2297
	0K2282	0K2284	0K2286	0K2288	0K2290	0K2296
PERF DATA	DM6151	DM6153	DM6155	DM6157	DM6159	DM6161
	DM6150	DM6152	DM6154	DM6156	DM6158	DM6160

EMERGENCY / RV / BUS

425 / 1450 2100	425 / 1550 2100	455 / 1550 2100
165-0615	165-0615	165-0621
425	425	455
41%	51%	44%
215-7821	215-7821	215-7823
15	15	16
0K1343	0K1344	0K1345
DM4826	DM4827	DM4828

ALL ARRANGEMENTS ABOVE HAVE COMMON IRON

C-12 9NS UPRATE - ABILITY AND COMPARISION CHART

9NS	335 / 1550 2100	355 / 1350 1800	355 / 1350 2100	380 / 1450 1800	380 / 1450 2100	395 / 1450 1800	395 / 1450 2100	410 / 1550 1800	410 / 1450 1800	410 / 1550 2100	410 / 1450 2100	430 / 1650 1800	430 / 1650 2100
CORE ARR.	148-2030	148-2020	148-2020	144-2905	144-2905	148-2021	148-2021	148-2023	148-2023	148-2023	148-2023	142-1997	142-1997
MAX H.P.	420	370	370	395	395	410	410	425	415	425	425	445	445
TORQ. RISE	85%	30%	52%	30%	52%	25%	46%	29%	21%	51%	41%	53%	31%
FLASH FILE	191-9926	191-9928	191-9928	191-9930	191-9930	191-9931	191-9931	191-9932	191-9932	191-9932	191-9932	191-9933	191-9933
INTER-LOCK	329	324	324	321	321	325	325	326	326	326	326	316	316
PERFORMANCE	2T9871	2T9857	2T9858	2T9593	2T9873	2T9859	2T9860	2T9861	2T9862	2T9863	2T9864	2T9549	2T9297
PERF DATA	DM3341	DM3328	DM3342	DM3329	DM3343	DM3330	DM3344	DM3331	DM3332	DM3345	DM3346	DM2787	DM2789

MULTI-TORQUE

9NS	355/410 MT	355/410 MT	355/410 MT	380/410 MT	380/430 MT
MULTI-TORQUE	1350/1550	1350/1450	1350/1450	1450/1550	1450/1650
	1800	1800	2100	1800	1800

CORE ARR.	148-2026	148-2026	148-2026	148-2028	148-2915
MAX H.P.	370/425	370/415	370/425	395/425	395/445
TORQ. RISE	30/29%	30/21 %	52/41 %	30/29%	30/31%
FLASH FILE	191-9937	191-9937	191-9937	191-9935	191-9938
INTER-LOCK	327	327	327	328	322
PERFORMANCE	2T9866	2T9868	0K0571	2T9870	2T9595
	2T9865	2T9876	0K0570	2T9869	2T9594
PERF DATA	DM3334	DM3336	DM2778	DM3338	DM3340
	DM3333	DM3335	DM2777	DM3337	DM3339

EMERGENCY / RV / BUS

425 / 1450 2100	425 / 1550 2100	455 / 1550 2100
--------------------	--------------------	--------------------

142-1999	142-1999	144-2925
425	425	455
41%	51%	44%
191-9934	191-9934	191-9929
330	330	320
2T9596	2T9402	2T9597
DM3347	DM2786	DM2790

SPECIAL RATING

355 / 1350 1800	208.5 FAN ON TEMP.
--------------------	-----------------------

148-2032
370
30%
191-9927
331
2T9872
DM2775

ALL ARRANGEMENTS ABOVE HAVE COMMON IRON

C-12 1YN UPRATE - ABILITY AND COMPARISION CHART

1YN	335 / 1550 2100	355 / 1350 1800	360 / 1450 2100	380 / 1450 1800	390 / 1450 2100	410 / 1550 1800	410 / 1450 1800	410 / 1550 2100	410 / 1450 2100
CORE ARR.G.	138-2585	117-0209	128-0332	117-0212	128-0337	117-0216	117-0216	128-0342	128-0342
MAX H.P.	420	370	375	395	405	425	415	425	425
TORQ. RISE	85%	30%	49%	30%	48%	29%	21%	51%	41%
FLASH FILE	190-0241	190-0233	190-0238	190-0234	190-0239	190-0232	190-0232	190-0237	190-0237
INTER-LOCK	315	302	307	303	308	301	301	306	306
PERFORMANCE	2T9111	2T7183	2T7550	2T6909	2T7551	2T6964	2T7139	2T7554	2T8948
PERF DATA	DM2753	DM1173	DM2138	DM2129	DM2139	DM2131	DM2130	DM2140	DM2751

MULTI-TORQUE

1YN MULTI-TORQUE	355/410 MT 1350/1550 1800	355/410 MT 1350/1450 1800	380 / 410 MT 1450/1550 1800
---------------------	---------------------------------	---------------------------------	-----------------------------------

CORE ARR.G.	126-0160	126-0160	126-0161
MAX H.P.	370/425	370/415	395/425
TORQ. RISE	30/29%	30/21 %	30/29%
FLASH FILE	190-0235	190-0235	190-0236
INTER-LOCK	304	304	305
PERFORMANCE	2T7560	2T7561	2T7549
	2T7552	2T7559	2T7553
PERF DATA	DM2132	DM2133	DM2136
	DM2134	DM2135	DM2137

EMERGENCY / RV

425 / 1550 2100	425 / 1450 2100
--------------------	--------------------

128-0415	128-0415
425	425
51%	41%
190-0240	190-0240
309	309
2T8949	2T7971
DM2752	DM2142

SPECIAL RATING

355 / 1350 1800	208.5 FAN ON TEMP.
--------------------	-----------------------

120-6612
370
30%
190-0242
323
2T9881
DM1173

ALL ARRANGEMENTS ABOVE HAVE COMMON IRON

C-10 3CS23000 - UP UPRATE - ABILITY AND COMPARISION CHART

3CS 12000-UP	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800		335 / 370 MT 1250/1350 1800
CORE ARR.G.	160-2318	160-2318	160-2318	132-3197	132-3197	165-0605	165-0605	136-4309		165-0607
MAX H.P.	320	320	315	350	350	366	365	385		350/385
TORQ. RISE	29%	50%	37%	27%	49%	32%	54%	25%		27/25%
FLASH FILE	215-7354	215-7354	215-7354	215-7355	215-7355	215-7357	215-7357	215-7358		215-7359
INTER-LOCK	20	20	20	21	21	22	22	23		24
PERFORMANCE	0K3827	0K3835	0K3834	0K3828	0K3836	0K3831	0K3837	0K3832		0K3830
										0K3829
PERF DATA	DM7127	DM7137	DM7136	DM7129	DM7133	DM7135	DM7128	DM7126		DM7132
										DM7130
TURBO	10R0183	10R0183	10R0183	10R0183	10R0183	10R0208	10R0208	10R0208		10R0208
WASTEGATED	NO	NO	NO	NO	NO	YES	YES	YES		YES

TURBO CHANGE REQUIRED - ONLY

TURBO CHART	
NON-WASTEGATE	
NEW	REMAN
204-6489	10R0183
204-8490	10R0183
WASTEGATED	
NEW	REMAN
204-6491	10R0208
204-6492	10R0208
204-6493 tucked	10R0357

C-10 3CS12000 - 22999 UPRATE - ABILITY AND COMPARISION CHART

3CS 12000-UP	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800	335 / 370 MT 1250/1350 1800
CORE ARR. G.	160-2318	160-2318	160-2318	132-3197	132-3197	165-0605	165-0605	136-4309	165-0607
MAX H.P.	320	320	315	350	350	366	365	385	350/385
TORQ. RISE	29%	50%	37%	27%	49%	32%	54%	25%	27/25%
FLASH FILE	220-6616	220-6616	220-6616	220-6617	220-6617	220-6619	220-6619	220-6620	220-6622
INTER-LOCK	10	10	10	11	11	12	12	13	14
PERFORMANCE	0K1951	0K1952	0K1953	0K1954	0K1955	0K1956	0K1957	0K1958	0K1960
									0K1959
PERF DATA	DM4836	DM4837	DM4838	DM4839	DM4840	DM4841	DM4842	DM4843	DM4845
									DM4844
TURBO	10R0183	10R0183	10R0183	10R0183	10R0183	10R0208	10R0208	10R0208	10R0208
WASTEGATED	NO	NO	NO	NO	NO	YES	YES	YES	YES

TURBO CHANGE REQUIRED - ONLY

TURBO CHART	
NON-WASTEGATE	
NEW	REMAN
204-6489	10R0183
204-8490	10R0183
WASTEGATED	
NEW	REMAN
204-6491	10R0208
204-6492	10R0208
204-6493 tucked	10R0357

C-10 3CS1 - 11999 UPRATE - ABILITY AND COMPARISION CHART

3CS1 - 11999	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800	335 / 370 MT 1250/1350 1800
CORE ARR.G.	160-2318	160-2318	160-2318	132-3197	132-3197	165-0605	165-0605	136-4309	165-0607
MAX H.P.	320	320	315	350	350	366	365	385	350/385
TORQ. RISE	29%	50%	37%	27%	49%	32%	54%	25%	27/25%
FLASH FILE	215-7806	215-7806	215-7806	215-7807	215-7807	215-7808	215-7808	215-7809	215-7810
INTER-LOCK	6	6	6	2	2	4	4	5	3
PERFORMANCE	0K2262	0K2263	0K2264	0K2265	0K2266	0K2267	0K2268	0K2269	0K2271
									0K2270
PERF DATA	DM6126	DM6127	DM6128	DM6129	DM6130	DM6131	DM6132	DM6133	DM6135
									DM6134
TURBO	10R0183	10R0183	10R0183	10R0183	10R0183	10R0208	10R0208	10R0208	10R0208
WASTEGATED	NO	NO	NO	NO	NO	YES	YES	YES	YES

TURBO CHANGE REQUIRED - ONLY

TURBO CHART	
NON-WASTEGATE	
NEW	REMAN
204-6489	10R0183
204-8490	10R0183
WASTEGATED	
NEW	REMAN
204-6491	10R0208
204-6492	10R0208
204-6493 tucked	10R0357

C-10 8YS UPRATE - ABILITY AND COMPARISION CHART

8YS	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1350 2100	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800
CORE ARR.G.	148-2013	148-2013	148-2013	148-2015	148-2015	148-2015	148-2017	148-2017	142-1998
MAX H.P.	320	320	315	350	350	350	366	365	385
TORQ. RISE	29%	50%	37%	27%	38%	49%	32%	54%	25%
FLASH FILE	191-9918	191-9918	191-9918	191-9921	191-9921	191-9921	191-9923	191-9923	191-9924
INTER-LOCK	325	325	325	326	326	326	327	327	328
PERFORMANCE	2T9847	2T9848	2T9849	2T9850	2T9851	2T9852	2T9853	2T9854	2T9401
PERF DATA	DM2791	DM2799	DM2797	DM2792	DM2793	DM2800	DM2794	DM3326	DM2788

MULTI-TORQUE	
8YS	335 / 370 MT
MULTI-TORQUE	1250 / 1350
	1800

SPECIAL RATING 208.5 FAN ON TEMP				
305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1350 1800	335 / 1350 2100

CORE ARR.G.	148-2019
MAX H.P.	350/385
TORQ. RISE	27/25%
FLASH FILE	191-9920
INTER-LOCK	329
PERFORMANCE	2T9856
	2T9855
PERF DATA	DM2796
	DM2795

148-2041	148-2041	148-2041	148-2043	148-2043
320	320	315	350	350
29%	50%	37%	27%	38%
191-9919	191-9919	191-9919	191-9922	191-9922
330	330	330	331	331
2T9940	2T9941	2T9942	2T9943	2T9944
DM2768	DM2770	DM2771	DM2772	DM2773

ALL ARRANGEMENTS ABOVE HAVE COMMON IRON

C-10 2PN UPRATE - ABILITY AND COMPARISION CHART

2PN	280 / 1050 1800	280 / 975 2100	305 / 1150 1800	305 / 1150 2100	325 / 1250 1800	325 / 1250 2100	335 / 1250 1800	335 / 1350 1800	350 / 1350 1800	370 / 1350 1800
CORE ARR.	117-0210	126-0169	117-0211	126-0170	126-0210	126-0171	119-3725	119-3725	117-0213	119-3759
MAX H.P.	295	295	320	320	340	340	350	350	366	385
TORQ. RISE	28%	39%	29%	50%	31%	53%	27%	38%	32%	25%
FLASH FILE	190-0224	190-0225	190-0226	190-0227	190-0229	190-0228	190-0221	190-0221	190-0220	190-0222
INTER-LOCK	305	306	307	308	310	309	302	302	301	303
PERFORMANCE	2T7562	2T7546	2T7563	2T7547	2T7725	2T7548	2T6943	2T7201	2T6910	2T6944
PERF DATA	DM1174	DM2126	DM1175	DM2127	DM2141	DM2128	DM1167	DM1168	DM1169	DM1170
INJECTORS - NEW	116-5424	116-5414	116-5424	116-5414	116-5424	116-5414	116-5414	116-5414	116-5414	116-5414
REMAN	0R4986	0R4987	0R4986	0R4987	0R4986	0R4987	0R4987	0R4987	0R4987	0R4987

MULTI-TORQUE	
2PN	335 / 370 MT
MULTI-TORQUE	1250 / 1350 1800

SPECIAL RATING 208.5 FAN ON TEMP

305 / 1150 1800	335 / 1250 1800	335 / 1350 1800
--------------------	--------------------	--------------------

CORE ARR.	126-0159
MAX H.P.	350/385
TORQ. RISE	27/25%
FLASH FILE	190-0223
INTER-LOCK	304
PERFORMANCE	2T7284 2T7283
PERF DATA	DM1171 DM1172
INJECTORS - NEW	116-5414
REMAN	0R4987

128-0802	119-3725	119-3725
320	350	350
29%	27%	38%
190-0231	190-0230	190-0230
307	302	302
2T9641	2T9642	2T9643
DM2758	DM2754	DM2755
116-5424	116-5414	116-5414
0R4986	0R4987	0R4987

INJECTOR CHANGE REQUIRED - ONLY

FLASH FILE PART NUMBER PROGRESSION

[illegible]

FLASH FILE PART NUMBER PROGRESSION

3CS 23000-UP	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800	335 / 370 MT 1250/1350		
Jan-02	215-7354	215-7354	215-7354	215-7355	215-7355	215-7357	215-7357	215-7358	215-7359		
Jul-01	208-5741	208-5741	208-7354	208-5742	208-5742	208-5743	208-5743	208-5744	208-5745		
3CS 12000-22999	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800	335 / 370 MT 1250/1350		
Mar-02	220-6616	220-6616	220-6616	220-6617	220-6617	220-6619	220-6619	220-6620	220-6622		
November 2000	198-3216	198-3216	198-3216	198-3217	198-3217	198-3218	198-3218	198-3219	198-3220		
November 1999	177-6987	177-6987	177-6987	177-6988	177-6988	177-6989	177-6989	177-6990	177-6991		
3CS1 - 11999	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800	335 / 370 MT 1250/1350		
Mar-02	215-7806	215-7806	215-7806	215-7807	215-7807	215-7808	215-7808	215-7809	215-7810		
November 2000	198-3276	198-3276	198-3276	198-3277	198-3277	198-3278	198-3278	198-3279	198-3280		
October 1999	177-9228	177-9228	177-9228	177-9229	177-9229	177-9230	177-9230	177-9231	177-9232		
8YS	305 / 1150 1800	305 / 1150 2100	305 / 1050 2100	335 / 1250 1800	335 / 1350 2100	335 / 1250 2100	350 / 1350 1800	350 / 1350 2100	370 / 1350 1800	335 / 370 MT 1250 / 1350	
October 2000-LOW NOX	191-9918	191-9918	191-9918	191-9921	191-9921	191-9921	191-9923	191-9923	191-9924	191-9920	
March 2000	191-2810	191-2810	191-2810	191-2812	191-2812	191-2812	191-2814	191-2814	191-2816	191-2817	
DECEMBER 1998	168-7009	168-7009	168-7009	168-7011	168-7011	168-7011	168-7012	168-7012	168-7008	168-7013	
2PN	280 / 1050 1800	280 / 975 2100	305 / 1150 1800	305 / 1150 2100	325 / 1250 1800	325 / 1250 2100	335 / 1250 1800	335 / 1350 1800	350 / 1350 1800	370 / 1350 1800	335 / 370 MT 1250 / 1350
DECEMBER 1999-LOW NOX	190-0224	190-0225	190-0226	190-0227	190-0229	190-0228	190-0221	190-0221	190-0220	190-0222	190-0223
March 1999	170-8077	170-8078	170-8079	170-8080	170-8082	170-8081	170-8074	170-8074	170-8073	170-8075	170-8076
MAY 1998	157-3046	157-3047	157-3048	157-3049	157-3055	1558676	1558670	1558670	1558671	1558672	1558674

C-10 Turbochargers

Parts Service Chart:

SER #	FORMER TURBO-BSC	FORMER REMAN TURBO	NEW TURBO-BSC	NEW REMAN TURBO	DESCRIPTION	WASTEGATE NON-WASTEGATE	WASTEGATE SETTING
2PN	127-8076	0R7060	208-4592	10R0448		NON-WASTEGATE	NON-WASTEGATE
8YS/ 3CS	144-0816 145-5183	0R7216 0R7216	204-6489 204-8490	10R0183 10R0183	LOW-MNT MID-MNT	NON-WASTEGATE NON-WASTEGATE	NON-WASTEGATE NON-WASTEGATE
3CS	165-7311 165-7313 172-6472 148-2016	0R7297 0R7297 NONE NONE	204-6491 204-6492 204-6493 NONE	10R0208 10R0208 10R0357	LOW-MNT MID-MNT TUCKED EURO II	WASTEGATE WASTEGATE WASTEGATE NON-WASTEGATE	28.0 PSI @ 1MM. 28.0 PSI @ 1MM. 28.0 PSI @ 1MM. NON-WASTEGATE

C-12 Turbochargers

Parts Service Chart:

SER #	FORMER TURBO-BSC	FORMER REMAN TURBO	NEW TURBO-BSC	NEW REMAN TURBO	DESCRIPTION	WASTEGATE NON-WASTEGATE	WASTEGATE SETTING
1YN	130-9201	0R-7084	190-6204	0R-7574		NON-WASTEGATE	NON-WASTEGATE
9NS	151-3082	0R7252	190-6205	0R-7575	LOW-MNT	WASTEGATE	24.0 PSI @ 1MM.
	151-5937	0R7252	190-6206	0R-7575	MID-MNT	WASTEGATE	24.0 PSI @ 1MM.
	162-6495	0R-7289	190-6207	0R-7576	LOW-MNT TUCKED	WASTEGATE	24.0 PSI @ 1MM.
	162-7603	0R-7603	190-6208	0R-7576	MID-MNT TUCKED	WASTEGATE	24.0 PSI @ 1MM.
2KS	164-9490	0R-7292	190-6210	0R-7578	LOW-MNT	WASTEGATE	22.6 PSI @ 1MM.
	164-9491	0R-7292	190-6211	0R-7578	MID-MNT	WASTEGATE	22.6 PSI @ 1MM.
	164-9493	0R-7293	190-6212	0R-7579	LOW-MNT TUCKED	WASTEGATE	22.6 PSI @ 1MM.
	164-9496	0R-7293	190-6213	0R-7579	MID-MNT TUCKED	WASTEGATE	22.6 PSI @ 1MM.
	150-7201	0R-7250	190-6209	0R-7577	EURO II	NON-WASTEGATE	NON-WASTEGATE